

## TECHNICAL FEATURES:

### STRUCTURE:

PVC for internal application (Polyvinyl chloride)

### THICKNESS:

From 200 to 350 microns

### PHYSICAL PROPERTIES:

Width 1220mm

Tear resistance: width 5.1 Kg/cm; length 0.6%

Elongation: 220%

Excellent resistance against abrasion, acids ethanol, salt (except xylene), stains, dirt, mould...

Dilatation after 48 hours at 65 ° C

Width: 0.9%

Length: 0.6%

Width: 262 Kg / cm

Length: 230 Kg / cm

### ADHESIVE:

Type: Activable acrylic, insensitive to humidity

The film is supposed to be installed on clean, smooth, rigid and non-porous surfaces (glass, metal, plastic, wood, laminated wood and so on).

Adhesive strenght:      20 minutes after installation: 1.04 Kg/cm  
                                    24 hours after installation: 1.43 Kg/cm  
                                    3 days after installation: 1.51 Kg/cm  
                                    7 days after installation: 1.65/cm

Adhesive strenght at high temperature 70°C:      After the 1st day: 1.37 Kg/cm  
    After 7 days: 1.03 Kg/cm

The ideal installing temperatures would be from 20 and 25°C (The min. is 12°C & the max. being 35°C)

Cover Styl' is a dry application with suitable squeegees solution.

The film can be removed with a heat gun or hair dryer (Min. 60°C).

WARRANTY: 10 years for internal installation against yellowing, cracking and delamination.

Our Primer or Primer + might be necessary for surfaces such as rough wood, plaster, concrete so on.

## STEPS TO USE PRIMER (WATER BASED) FOR COVER STYL FILMS :

- 1/ Clean and degrease the surface to be treated. Remove the asperities.
- 2/ Apply the PRIMER with roller on the dry surface
- 3/ Let dry the PRIMER before applying the Cover Styl film :
  - PRIMER can be used between 15 ° C and 30 ° C (room temperature)
  - Close well the can after each usage
  - Don't leave PRIMER in the places in which children can reach it
  - In case of contact with eyes, rinse immediately with water and contact your doctor